REMARKS

11. (currently amended) A device for scanning an optical record carrier having a transparent layer and an information layer, comprising

- a radiation source for generating the radiation beam,
- an objective lens system for converging the radiation beam through the transparent layer to a focus on the information layer,
- a detection system for intercepting radiation from the record carrier, and
- an optical wavefront modifier according to claim 9 is arranged in the optical path between the radiation source and the detection system, wherein the first and second directions of displacement are chosen to compensate for expected motions of the objective lens system during operation.

12. (previously presented) The device of claim 10, wherein the difference between a first electric signal supplied to the first electrode layer and a second electric signal supplied to the second electrode layer is substantially proportional to a displacement of the objective lens system.

13. (previously presented) The device of claim 11, wherein the difference between a first electric signal supplied to the first electrode layer and a second electric signal supplied to the second electrode layer is substantially proportional to a displacement of the objective lens system.

REMARKS

14. (previously presented) A method for modifying a radiation beam in a scanning device for an optical record carrier, the method comprising:

- using a wavefront modifier comprising
  - at least first and second transparent electrode layers, at least one of the layers having a center of symmetry that is displaced from a center of symmetry of the modifier as a whole;
  - a medium for modifying the wavefront in dependence on electrical excitation from the electrodes;
- adjusting voltage of one or both electrodes to alter an effect of the wavefront modifier to compensate for expected motion of an objective lens system of the scanning device; and
- receiving and modifying a radiation beam using the modifier with the altered effect.

15. (currently amended) An optical wavefront modifier for modifying a wavefront of an optical beam passing through the modifier, the modifier comprising

- at least first and second transparent electrode layers, at least the first electrode layer comprising three or more electrodes of a transparent, conductive material, wherein the electrodes within each layer are arranged around a center of symmetry and a width of the electrodes decreases with increasing radius from the center; and
- at least one medium for modifying the wavefront in dependence on electrical excitation of the medium, the medium being arranged between the electrode layers.

REMARKS

16. (previously presented) The modifier of claim 15, wherein, within at least one of the electrode layers comprises 2N+1 strips numbered consecutively with an index j that runs as N, -N+1,... , 0, 1, ..., N, and the strip with index j covers an area in the (x,y) plane that complies with

$$\frac{2j-1}{2N+1} < W_{31}(x,y) < \frac{2j+1}{2N+1}$$

where $W_{31}(x,y) = (x^2+y^2)x$ is the Seidel polynomial for coma, and x,y are normalized coordinates in the cross-section of the radiation beam in the plane of the compensator, where x is in the direction of displacement of an objective lens system of a device in which the compensator is to be disposed.

17. (new) An optical wavefront modifier for modifying a wavefront of an optical beam passing through the modifier, the modifier comprising

- at least first and second transparent electrode layers, at least the first electrode layer comprising three or more electrodes of a transparent, conductive material, wherein a difference between
    - a maximum value taken by the aberration function in the area occupied by an electrode and
    - a minimum value taken by the aberration function in the area occupied by that electrode

  is substantially equal for all electrodes of the wavefront modifier; and
- at least one medium for modifying the wavefront in dependence on electrical excitation of the medium, the medium being arranged between the electrode layers.

REMARKS

The present supplemental amendment adds a claim commensurate with the scope of the disclosure and corrects minor typographical errors in previously presented claims. No claim is narrowed herein.

Please charge any fees other than the issue fee to deposit account 14-1270. Please credit any overpayments to the same account.

Applicants respectfully submit that they have answered each issue raised by the Examiner and that the application is accordingly in condition for allowance. Allowance is therefore respectfully requested.

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited this date with the United States Postal Service as first class mail in an envelope addressed to

Mail Stop _____
Commissioner for Patents
P.O. Box 1450
Alexandria VA 22313-1450

On _____ _____ _____(date)
By_____ _____ _____(signature)

Respectfully submitted,

By_____
Anne E. Barschall, Reg. No. 31,089
Tel. no. 914-332-1019
Fax no. 914-332-7719
April 15, 2004